SYMPOSIUM:
  2nd International Symposium on Spacecraft Ground Control and Data Systems

TITLE:
  "An Object-oriented Interface to the CCSDS Ground Telecommand Services"

ABSTRACT:

The Telecomand Data Routing and Channel Services defined by the Consultative
Committee for Space Data Systems (CCSDS) are flexible enough to support a
myriad of commanding models. Because the standard is so broad, the
traditional approach has been to implement only the portion of the standard
needed by the particular spacecraft being tested/operated.

Tasked with providing Telecommand Services for an entire class of spacecraft,
where each spacecraft may choose any valid CCSDS commanding model, NASA
Code 584 designed a common architecture capable of handling the full CCSDS
protocol.

The solution uses another CCSDS standard - the Standard Formatted Data Unit
(SFDU) as the interface to the Telecommand Services. SFDUs provide a
consistent way of labelling data objects, as well as allowing data objects to
encapsulate other data objects. The resulting interface is:

  - Flexible: The full Data Routing and Channel Services are available via
        a single interface. The client (i.e. the command source) may
        enter commands at any layer within the protocol stack, specify
        any of the data aggregation or segmentation methods, and dynamically
        set any configuration parameter defined in the standard.

  - Object-oriented: Each object specifies both the data and the actions
        to be performed with the data. An object may contain other objects.

  - Expandable: New capabilities are added by defining new objects.
        Objects pass thru the protocol layers until they reach the
        applicable layer.

The resulting design is:

  - Modular: The logic for each protocol layer is contained in a separate
        Application Program Interface (API). The objects used for the
        external interface are also used for communication between layers.

  - Distributable: The design can be split along any layer boundary
        for distribution across multiple machines. The objects ensure
        data consistency across platforms.

  This paper describes the SFDU-based interface and the resulting protocol
implementation. The implementation is currently used by NASA (National
Aeronautics and Space Administration) for integration & test of the Microwave
Anisotropy Probe (MAP) and Earth Observer-1 (EO-1) spacecraft. It will be
used for post-launch operations of these spacecraft as well as the Imager
for Magnetopause to Aurora Global Exploration (IMAGE) spacecraft.

AUTHORS:

Timothy Joseph Ray (NASA GSFC)
  Mailing address:
    NASA
    Goddard Space Flight Center
    Mailstop 410.4
    Greenbelt, MD 20771 USA
  e-mail: Timothy.J.Ray.1@gsfc.nasa.gov
  telephone: 301-286-0581
  fax: 301-286-0241

Jeffrey Todd Condron (Raytheon STX)
  Mailing address:
    NASA
    Goddard Space Flight Center
    Mailstop 565.0
    Greenbelt, MD 20771 USA
  e-mail: Jeffrey.T.Condron.1@gsfc.nasa.gov
  telephone: 301-286-1367
  fax: 301-286-0241